

# **BUILT-IN**

## VENTILATION

### INTRODUCTION

BUILT-IN seems only a grille but behind it is a range of high performance extract/intake wall axial fans designed to fit through most wall thicknesses using telescopic liners supplied. Ideal solution for commercial premises in white or appealing coloured front grille for a brilliant fusion of efficiency and style.

### CONSTRUCTION

- Extract/Intake model available in 2 sizes: 9" and 12" (with same wall hole size).
- Suitable for residential and commercial applications.
- Stylish profile of inner and outer grilles for an unobtrusive installation.
- Silent shutter operation via thermal actuator.
- Finger guarded and IPX4 protected internal and external grilles, manufactured in shockproof high quality technopolymer.
- Designed for a time saving installation.
- Easy cleaning: the integrated components can be easily disassembled for cleaning.
- Maintenance free, self-lubricating sleeve bearing motor for long life and noiseless running.
- Thermal protected induction motor, 230V 50Hz.
- Speed controllable via RVS/R controller, included.
- Fans comply with En 60335-2-80, EC Low Voltage
   Directive 73/73 93/68 and EC Directive EMC89/336.

### **ENERGY SAVING**

P.I.R, humidistat and Air Quality Sensors are available accessories to provide energy saving by switching the fan on when needed and when the room is occupied.




Luft Industries Natal (Pty) Ltd
21 Aloefield Crescent, Springfield Park, Durban.
Tel: +27 31 579-3999 • Fax: +27 31 579-2999 • Email: info@luft.co.za
Website: www.luft.co.za





FAN DIMENSIONS in mm									
MODEL	A B C		С	D	Kg				
BUILT-IN	430	430	190-380	370	11.5/12.5				



FAN SPECIFICATION									
MODEL	m³/h	l/s	Pa	W	dBA@3m	protection			
BUILT-IN 9	750/480	208/133	46/35	46/36	55	IPX4			
BUILT-IN 12	1630/850	453/236	75/49	106/84	54	IPX4			

# FAN PERFORMANCE BUILT- IN 9 10 20 10 20 10 20 30 40 50 60 80 100 100 200 400 600 800 1000 1200 1400 1600 1800 m3/h

The higher air volume and solid blue fan curve line refer to the extract mode on the 9" and 12" models.
The lower air volume and dotted red fan curve line refer to the intake mode on the 9" and 12" models.